



PLS-45 • PLS-45W

PLS-60 • PLS-60W

PLS-100 • PLS-100W


Planers
For Skid steer loaders
from 2.5 to 5 t

PLE-30

PLE-45

PLE-60

Planers
For excavators
from 3 to 22 t



Planers

For Skid steer loaders :

- ▶ Efficient to remove asphalt and concrete surfaces, also in narrow areas.
- ▶ Independent self-levelling system for both right and left slides to have constant planing depth in all the situations.
- ▶ Independent depth adjustment on right and left side : possibility to create inclined surfaces up to 16°.
- ▶ Easy maintenance : easy change of planing drums.
- ▶ W Model: Model with 110 liter water tank embedded in frame : reduce the dust and increase the teeth durability.
- ▶ Lateral shift: up to 650 mm.



MODEL		PLS-45	PLS-45W	PLS-60	PLS-60W	PLS-100	PLS-100W
Skid-steer weight	t	2.5 - 4.5		3.2 - 4.5		3.2 - 5	
Supply flow	l/min	65 - 140		85 - 160		95 - 200	
Operating weight	kg	700	820	850	980	1060	1220
Operating pressure	bar	300 - 140		300 - 150		350 - 140	
Planing depth	mm	0 - 150		0 - 170		0 - 130	
Planing width	mm	450		600		1000	
Average planing speed (50 % of depth)	mm/min	1000 - 5000		900 - 4000		800 - 4000	

For excavators :

- ▶ To remove everywhere asphalt and concrete.
- ▶ Ideal for planing and cutting all surfaces : horizontal, vertical, inclined, also in tunnels' vault.
- ▶ Built-in protection preventing stones from being thrown outwards even when working overhead.
- ▶ Direct drive hydraulic piston motor ensures high performance and minimum heating.



MODEL		PLE-30	PLE-45	PLE-60
Excavator weight	t	3 - 6	6 - 12	12 - 22
Supply flow	l/min	40 - 75	65 - 140	90 - 200
Operating weight	kg	335	580	940
Operating pressure	bar	300 - 140	300 - 140	300 - 140
Dimensions :	A. Length	mm	950	1150
	B. Height	mm	700	760
	C. Width	mm	450	715
	E. planing depth	mm	0 - 100	0 - 150
	F. planing width	mm	300	450
Average planing speed	mm/min	400 - 2500	800 - 4000	800 - 4000



Montabert SAS

203, route de Grenoble
69800 St Priest, France

Tel. +33-(0)4 72 22 97 97 Fax. +33-(0)4 72 22 97 56
montabert_marketing@eu.irco.com

www.montabert.com

Nothing contained in this brochure is intended to extend any warranty or representation expressed or implied, regarding the products described herein. Any such warranties or other terms and conditions of sale products shall be in accordance with Ingersoll Rand standards terms and conditions of sales for such products, which are available upon request. Specifications and machines can be modified at any time and without notice.