

### **Main Features of skid steer loader:**

- 1) Good technical parameters with competitive price
- 2) maneuver in tight spaces, turn within its own length
- 3) a broad product line, innovative designs, and unsurpassed range of job-matched attachments.
- 4) Excellent reach & lift height for truck loading (vertical path).
- 5) more than 20 series attachments for option: pallet fork, swing blade, utilityfork grapple, asphalt cutter, backhoe, hydraulic hammer, 4 in 1 bucket, auger, cultivator, and tooth bucket etc
- 6) attachment can be used with bobcat type skid loader
- 7) world famous hydraulic systems from America, Japan and Italy
- 8) famous brand engine with EPA or EC stage II or III from abroad and domestic
- 9) CE and ISO 9001 certificated
- 10) versatility, maneuverability and reliability



Hydraulic system imported from abroad

Patented design of chassis

Digital Instrument Panel



Rops/FopsRops/Fops CABIN WITH EAS MAINTENANCE DESIGN

Design for Safety

Same Quick-Attach system fits for most famous brands

**OPTIONAL:**

- 1)PERKINS ENGINE, HYUNDAI ENGINE, DEUTZ ENGINE, LOVOLE ENGINE AND DOMESTIC ENGINE AND MORE
- 2)WITH OR WITHOUT HYDRAULIC SERVO(JOYSTICK SYSTEM)
- 3)ENCLOSED CAB WITH OR WITHOUT AIR CONDITIONER OR HEATER
- 4)ALL KINDS OF TIRES ( SOLIC, NORMAL, CACUUM) AND DIFFERENT TYPE FOR CHOICE
- 5)VARIOUS OF ATTACHMENTS

<b>Specifications</b>	JC60
Rated Operating Capacity	850
Tipping load (Kg)	1700
Bucket Capacity(m <sup>3</sup> )	0.4-0.5
Hydraulic	75
Engine power(Hp)	60
Weight (Kg)	3000
Max.Travel Speed(km/h)	10
Grade ability (°)	20
Tyre	12-16-15 N.H.S
Fuel/hyd.oil capacity (L)	60/60

<b>Dimensions</b>	JC60
A. Height at Maximum Extension	3670mm
B. Hinge Pin Height	2900mm
C. Total Height	2030mm
D. Length with Bucket	3200mm
E. Length without Bucket	2450mm
F. Width with Bucket	1740mm
G. Track Width	1450mm
H. Wheelbase	991mm
J. Ground Clearance	185mm

K. Dump Angle 45°C

L. Dumping Height 2310mm

M. Maximum Reach 710mm

### Dimensional Drawings

