

## TRACKED MINITRANSPORTER WITH HYDRAULIC TIPPING FARM BODY AND EXTENSIBLE SIDES

## MODEL

954.AMTI-5.0C-

Tipping farm body with removable and/or extensible sides for the transport of all types of materials, from lumber to fruit crates, hay or aggregate



MACHINE DIMENSIONS		
Max height	119 cm	
Max width	76 cm	
Max length (operator platform closed)	177 cm	
Tracks	180 x 60 x 38 mm	
Track width	74 cm	

WEIGHTS	
Payload	500 kg
Payload on gradients in excess of 30%	350 kg
Dry weight	377 kg

TRANSMISSION	
Туре	Hydraulic
Speed	Slow 2.1 km/h Fast 4.8 km/h
Tipping	Hydraulic
Max pressure	160 bar

FARM BODY DIMENSIONS		
Length of bed with sides closed/open	100/110 cm	
Width of bed with sides closed/open	70/90 cm	
Height of sides	46 cm	

POWER UNITS	HORSEPOWER	CODE
Honda petrol engine with manual/electric starting	9 hp	G09H/GE09H
Axo petrol engine with manual/electric starting	9 hp	G09/GE09
Axo diesel engine with manual/electric starting	7 hp	D07/DE07
Yanmar diesel engine with manual/electric starting	7 hp	D07Y/DE07Y
MYT100 Electric motor, 230 V power supply	3 kW	MYT100